








Quarz-Programm von Hong Kong X'tals bei Bindel Elektronik AG ab Lager lieferbar

HC 49 U		
	HKC Typ:	9U
	Toleranz:	30ppm
	Temp. Bereich	-10 - + 60°C
	Löten:	THT
Frequenz MHz	pF	Bindel Nr.
4.000000	12 pF	806137
4.194304	12 pF	806070
4.433619	Serial	806071
6.000000	16 pF	806072
7.372800	16 pF	806138
8.000000	30 pF	806073
10.240000	18 pF	806074
13.522500	20 pF	806075
13.560000	30 pF	806076
16.000000	30 pF	806077
20.000000	18 pF	806139
24.576000	12 pF	806078
54.000000	10 pF	806079

HC 49 US		
	HKC Typ:	9S
	Toleranz:	30ppm
	Temp. Bereich	-10 - + 60°C
	Löten:	THT
Frequenz	pF	Bindel Nr.
3.250000	20 pF	806080
4.000000	18 pF	806140
4.194304	12 pF	806081
4.332000	20 pF	806082
4.915200	Serial	806147
5.000000	20 pF	806144
6.000000	Serial	806085
7.200000	10 pF	806086
7.680000	30 pF	806087
8.000000	20 pF	806088
9.830400	30 pF	806089
10.000000	12 pF	806090
11.059200	Serial	806091
12.000000	32 pF	806092
13.560000	20 pF	806093
14.318180	20 pF	806094
14.745600	20 pF	806095
16.000000	30 pF	806165
16.934400	30 pF	806098
17.734475	10 pF	806097
18.000000	22 pF	806099
18.432000	Serial	806100
19.660800	18 pF	806101
20.000000	20pF	806102
20.480000	18pF	806104
22.118400	16pF	806105
24.000000	32pF	806160
24.576000	18 pF	806106
25.000000	18 pF	806108
27.000000	16 pF	806109

HC 49 SMD		
	HKC Typ:	SS
	Toleranz:	30ppm
	Temp. Bereich	-10 - + 60°C
	Löten:	SMD
Frequenz	pF	Bindel Nr.
3.250000	20 pF	806111
4.000000	18 pF	806141
4.194304	12 pF	806112
4.332000	20 pF	806113
4.500000	20 pF	806114
4.915200	Serial	806143
5.000000	20 pF	806115
6.000000	Serial	806145
7.200000	10 pF	806116
7.372800	20 pF	801190
7.680000	30 pF	806149
8.000000	20 pF	806150
9.830400	30 pF	806117
10.000000	12 pF	806118
11.059200	Serial	806151
12.000000	32 pF	806154
13.560000	20 pF	806119
14.318180	20 pF	801120
14.745600	20 pF	801291
16.000000	30 pF	801304
16.934400	30 pF	806122
17.734475	10 pF	806123
18.000000	22 pF	806124
18.432000	Serial	806125
19.660800	18 pF	806155
20.000000	20 pF	806156
24.480000	18 pF	806126
22.184000	16 pF	806127
24.000000	32 pF	806157
24.576000	18 pF	806128
25.000000	20 pF	806158
27.000000	16 pF	806129
30.000000	20 pF	806159

5032		
	HKC Typ:	CA
	Toleranz:	30ppm
	Temp. Bereich	-10 - + 60°C
	Löten:	SMD
Frequenz	pF	Bindel Nr.
8.000000	10 pF	806130
9.830400	10 pF	806131
12.000000	8 pF	806132
13.521270	10 pF	806133
14.745600	16 pF	806134
15.360000	18 pF	806135
24.000000	20 pF	806136

Uhrenquarze 32.768 KHz		
	Toleranz:	20ppm
	Temp. Bereich	-20 - + 70°C
	Lastkapazität	12.5 pF
Abbildung	Typ	Bindel Nr.
	2T	806162
	3T	806163
	M3	806164